

Hi Power 60W PoE injector



Key Features

- Up to 60W of PoE Power on 4-Pairs
- IEEE802.3af/at Compliant with Higher Power
- Safe on Low Power Devices receive only the power they Need
- Remote power feeding up to 100meters
- Automatic Detection and protection of Non-Standard Ethernet Terminals
- Safe: Low Power Devices Receive only the Power They Need 2-pair PDs receive Power On 2-pairs
- Support 10/100/1000Base-T applications
- PTZ Cameras and Access Points Compliant 802.3af/at
- Cost effective replacement for PD-9501G or POE60U-560G

Specifications

Model	PSE156G
Standards	IEEE802.3 10Base-T IEEE802.3u 100Base-T IEEE802.3ab 1000Base-T IEEE802.3af/at Compliant
PoE pin	1/2(+), 3/6(-) spare 4/5(+),7/8(-)
PoE Output	54-57VDC Maximal / PoE Power Max 60W
Input Power	100~240VAC 50/60Hz
Dimensions	180mm(D) X 77mm(W) X 37mm(H)
Indicators	Power Led(side) / PoE Led
Operating Temp/Humidity	0~45°C / Maximum 95% Non-condensing
Storage Temp	-10~45°C / Maximum 95% Non-condensing
Certifications	FCC/CE/KC ROHS
Warranty	1year