



Main Features

- IEEE802.3af/at Power of Ethernet compliant
- supported console Management and Web management Support
- Up to 30W Power on
- 10/100/1000Mbps Auto-Negotiation / Auto MDI/MDIX

Specifications	
Model number	SL-S3010PH
Port	8port 10/100/1000M / Uplink Port 2 x SFP Port 8ports Support PoE
Standards	IEEE802.3 10Base-T IEEE802.3u 100Base-T IEEE802.3ab 1000Base-T IEEE802.3z 1000Base-X IEEE802.3x flow control IEEE802.3af/at Power of Ethernet compliant
IEEE802.3af	Support 15.4W (8Port)
IEEE802.3at	Support 30W (4Port only)
LED indicator	Power, Link/Act, 100/1000Mbps, PoE Status
Dimension(W*D*H)	280mm*180mm*44mm
Working Environment	Working temperature: 0~40C Storing temperature: -10~70C Working humidity: 10%~90%(no condense) Storing humidity: 5%~90%(no condense)

Input Power	100~240VAC 50/60Hz
Output Power	55VDC Maximal / 300~600mA / PoE Power Max 130W
Power Pin	1/2(+) , 3/6(-) Endspan (Mode A)
Certifications	FCC/CE/KC ROHS
Mac/Jumbo Frame	8K/9K
DRAM/FLASH	128MB/16MB
Switching Capacity	20Gbps
Management	VLAN/IGMP/STP/Link aggregation/ACL/QoS/802.1x/SNMP/RMON LLDP/DHCP Snooping
Access	HTTP/HTTPS/Console/Telnet
Warranty	1Year